



Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 13

LOCTITE SF 7471 known as LOCTITE 7471 150ml EN

SDS No. : 179503
V002.8

Revision: 22.05.2015
printing date: 26.11.2017

Replaces version from: 05.05.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SF 7471 known as LOCTITE 7471 150ml EN

Contains:

Acetone

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Primer, containing solvents

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

| | |
|---|------------|
| Flammable aerosols | Category 1 |
| H222 Extremely flammable aerosol. | |
| H229 Pressurised container: May burst if heated. | |
| Serious eye irritation | Category 2 |
| H319 Causes serious eye irritation. | |
| Specific target organ toxicity - single exposure | Category 3 |
| H336 May cause drowsiness or dizziness. | |
| Target organ: Central Nervous System | |
| Chronic hazards to the aquatic environment | Category 3 |
| H412 Harmful to aquatic life with long lasting effects. | |

2.2. Label elements

Label elements (CLP):

| | |
|--|--|
| Hazard pictogram: |  |
| Signal word: | Danger |
| Hazard statement: | H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects. |
| Supplemental information | EUH066 Repeated exposure may cause skin dryness or cracking. Contains Benzothiazole-2-thiol. May produce an allergic reaction. |
| Precautionary statement: | P251 Do not pierce or burn, even after use. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P211 Do not spray on an open flame or other ignition source. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P102 Keep out of reach of children. ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements*** |
| Precautionary statement: Prevention | P261 Avoid breathing spray. P273 Avoid release to the environment. |
| Precautionary statement: Response | P337+P313 If eye irritation persists: Get medical advice/attention. |

2.3. Other hazards

The aerosol container is under pressure. Do not expose to high temperatures.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:

Primer, containing solvents

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. | EC Number REACH-Reg No. | content | Classification |
|-----------------------------------|-------------------------------|-----------------|--|
| Acetone 67-64-1 | 200-662-2 01-2119471330-49 | >= 75- <= 100 % | Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336 |
| Propane 74-98-6 | 200-827-9 01-2119486944-21 | >= 10- < 25 % | Flam. Gas 1 H220 Press. Gas H280 |
| Propan-2-ol 67-63-0 | 200-661-7 01-2119457558-25 | >= 10- < 20 % | Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336 |
| Benzothiazole-2-thiol 149-30-4 | 205-736-8 | >= 0,3- < 1 % | Skin Sens. 1 H317 Aquatic Chronic 1 H410 Aquatic Acute 1 H400 |

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Vapors may cause drowsiness and dizziness.

EYE: Irritation, conjunctivitis.

Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

5.2. Special hazards arising from the substance or mixture

None

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas.

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place.

Keep away from heat and direct sunlight.

7.3. Specific end use(s)

Primer, containing solvents

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-------|-------------------|-----------------------------------|--|-----------------|
| Acetone 67-64-1 [ACETONE] | 500 | 1.210 | Time Weighted Average (TWA): | | EH40 WEL |
| Acetone 67-64-1 [ACETONE] | 1.500 | 3.620 | Short Term Exposure Limit (STEL): | | EH40 WEL |
| Acetone 67-64-1 [ACETONE] | 500 | 1.210 | Time Weighted Average (TWA): | Indicative | ECLTV |
| Propan-2-ol 67-63-0 [PROPAN-2-OL] | 500 | 1.250 | Short Term Exposure Limit (STEL): | | EH40 WEL |
| Propan-2-ol 67-63-0 [PROPAN-2-OL] | 400 | 999 | Time Weighted Average (TWA): | | EH40 WEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|------------------------|---------------------------------|-----------------|-------|-----|------------|----------------|---------|
| | | | mg/l | ppm | mg/kg | others | |
| Acetone 67-64-1 | aqua (intermittent releases) | | | | | 21 mg/L | |
| Acetone 67-64-1 | STP | | | | | 100 mg/L | |
| Acetone 67-64-1 | sediment (freshwater) | | | | 30,4 mg/kg | | |
| Acetone 67-64-1 | sediment (marine water) | | | | 3,04 mg/kg | | |
| Acetone 67-64-1 | soil | | | | 29,5 mg/kg | | |
| Acetone 67-64-1 | aqua (freshwater) | | | | | 10,6 mg/L | |
| Acetone 67-64-1 | aqua (marine water) | | | | | 1,06 mg/L | |
| Propan-2-ol 67-63-0 | aqua (freshwater) | | | | | 140,9 mg/L | |
| Propan-2-ol 67-63-0 | aqua (marine water) | | | | | 140,9 mg/L | |
| Propan-2-ol 67-63-0 | sediment (freshwater) | | | | 552 mg/kg | | |
| Propan-2-ol 67-63-0 | sediment (marine water) | | | | 552 mg/kg | | |
| Propan-2-ol 67-63-0 | soil | | | | 28 mg/kg | | |
| Propan-2-ol 67-63-0 | aqua (intermittent releases) | | | | | 140,9 mg/L | |
| Propan-2-ol 67-63-0 | STP | | | | | 2251 mg/L | |
| Propan-2-ol 67-63-0 | oral | | | | | 160 mg/kg food | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|------------------------|--------------------|-------------------|---|---------------|------------------------|---------|
| Acetone 67-64-1 | Workers | Inhalation | Acute/short term exposure - local effects | | 2420 mg/m ³ | |
| Acetone 67-64-1 | Workers | Dermal | Long term exposure - systemic effects | | 186 mg/kg bw/day | |
| Acetone 67-64-1 | Workers | Inhalation | Long term exposure - systemic effects | | 1210 mg/m ³ | |
| Acetone 67-64-1 | general population | Dermal | Long term exposure - systemic effects | | 62 mg/kg bw/day | |
| Acetone 67-64-1 | general population | Inhalation | Long term exposure - systemic effects | | 200 mg/m ³ | |
| Acetone 67-64-1 | general population | oral | Long term exposure - systemic effects | | 62 mg/kg bw/day | |
| Propan-2-ol 67-63-0 | Workers | Dermal | Long term exposure - systemic effects | | 888 mg/kg bw/day | |
| Propan-2-ol 67-63-0 | Workers | Inhalation | Long term exposure - systemic effects | | 500 mg/m ³ | |
| Propan-2-ol 67-63-0 | general population | Dermal | Long term exposure - systemic effects | | 319 mg/kg bw/day | |
| Propan-2-ol 67-63-0 | general population | Inhalation | Long term exposure - systemic effects | | 89 mg/m ³ | |
| Propan-2-ol 67-63-0 | general population | oral | Long term exposure - systemic effects | | 26 mg/kg bw/day | |

Biological Exposure Indices:
None**8.2. Exposure controls:**

Respiratory protection:
Use only in well-ventilated areas.
Filter type: P2

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; ≥ 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Wear protective glasses.

Skin protection:
Wear suitable protective clothing.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|--|------------------------------------|
| Appearance | Aerosol |
| | yellow |
| Odor | pungent |
| Odour threshold | No data available / Not applicable |
| pH | Not applicable |
| Initial boiling point | 56 °C (132.8 °F) |
| Flash point | Not applicable |
| Decomposition temperature | No data available / Not applicable |
| Vapour pressure (20 °C (68 °F)) | 230 mm hg |
| Density (ρ) | 0,8 g/cm ³ |
| Bulk density | No data available / Not applicable |
| Viscosity | No data available / Not applicable |
| Viscosity (kinematic) | No data available / Not applicable |
| Explosive properties | No data available / Not applicable |
| Solubility (qualitative) (Solvent: Water) | Miscible |
| Solubility (qualitative) (Solvent: Acetone) | Soluble |
| Solidification temperature | No data available / Not applicable |
| Melting point | No data available / Not applicable |
| Flammability | No data available / Not applicable |
| Auto-ignition temperature | No data available / Not applicable |
| Explosive limits | No data available / Not applicable |
| Partition coefficient: n-octanol/water | No data available / Not applicable |
| Evaporation rate | No data available / Not applicable |
| Vapor density | No data available / Not applicable |
| Oxidising properties | No data available / Not applicable |

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity**10.1. Reactivity**Reaction with strong acids.
Reacts with strong oxidants.**10.2. Chemical stability**

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable

10.5. Incompatible materials

See section reactivity

10.6. Hazardous decomposition products

Irritating organic vapours.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****General toxicological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

STOT-single exposure:

May cause drowsiness or dizziness.

Oral toxicity:

This material is considered to have low toxicity if swallowed.

Inhalative toxicity:

May cause headache and dizziness.

Skin irritation:

Solvent may remove essential oils from the skin making it susceptible to attack from other chemicals.
Prolonged or repeated contact may cause skin irritation.

Eye irritation:

Causes serious eye irritation.

Sensitizing:

May cause allergic reaction.

Acute oral toxicity:

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|---------------------------------|---------------|-------------|-------------------------|------------------|---------|--------|
| Acetone 67-64-1 | LD50 | 5.800 mg/kg | oral | | rat | |
| Propan-2-ol 67-63-0 | LD50 | 5.338 mg/kg | oral | | rat | |

Acute inhalative toxicity:

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|---------------------------------|---------------|-----------|-------------------------|------------------|---------|--------|
| Acetone 67-64-1 | LC50 | 76 mg/l | | 4 h | rat | |
| Propan-2-ol 67-63-0 | LC50 | 72,6 mg/l | | 4 h | rat | |

Acute dermal toxicity:

| Hazardous components CAS-No. | Value type | Value | Route of application | Exposure time | Species | Method |
|---------------------------------|---------------|----------------|-------------------------|------------------|---------|--------|
| Acetone 67-64-1 | LD50 | > 15.688 mg/kg | dermal | | rabbit | |
| Propan-2-ol 67-63-0 | LD50 | 12.870 mg/kg | dermal | | rabbit | |

Skin corrosion/irritation:

| Hazardous components CAS-No. | Result | Exposure time | Species | Method |
|---------------------------------|---------------------|------------------|---------|---|
| Propan-2-ol 67-63-0 | slightly irritating | 4 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |

Serious eye damage/irritation:

| Hazardous components CAS-No. | Result | Exposure time | Species | Method |
|---------------------------------|-----------------------|------------------|---------|---|
| Acetone 67-64-1 | irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |
| Propan-2-ol 67-63-0 | moderately irritating | | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

| Hazardous components CAS-No. | Result | Test type | Species | Method |
|-----------------------------------|-----------------|------------------------------|------------|---|
| Propan-2-ol 67-63-0 | not sensitising | Buehler test | guinea pig | |
| Benzothiazole-2-thiol 149-30-4 | sensitising | Buehler test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |
| Benzothiazole-2-thiol 149-30-4 | sensitising | Guinea pig maximisation test | guinea pig | OECD Guideline 406 (Skin Sensitisation) |

Germ cell mutagenicity:

| Hazardous components CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|-----------------------------------|------------------------------------|--|--|---------|--|
| Acetone 67-64-1 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Propane 74-98-6 | negative with metabolic activation | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Propan-2-ol 67-63-0 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | |
| Benzothiazole-2-thiol 149-30-4 | negative | intraperitoneal | | mouse | Micronucleus assay |

Repeated dose toxicity

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Method |
|-----------------------------------|--------------------|----------------------------|--|---------|--------|
| Acetone 67-64-1 | NOAEL=2500 ppm | oral: drinking water | 13 weeks | rat | |
| Acetone 67-64-1 | LOAEL=5000 ppm | oral: drinking water | 13 weeks | rat | |
| Propan-2-ol 67-63-0 | NOAEL=1500 | inhalation | 13 weeks 6 hours/day, 5 days/week | mouse | |
| Propan-2-ol 67-63-0 | LOAEL=5000 | inhalation | 13 weeks 6 hours/day, 5 days/week | mouse | |
| Benzothiazole-2-thiol 149-30-4 | LOAEL=750 mg/kg | oral: gavage | 13 weeks 5 days/week | rat | |
| Benzothiazole-2-thiol 149-30-4 | NOAEL=375 mg/kg | oral: gavage | 13 weeks 5 days/week | rat | |

SECTION 12: Ecological information**General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity**Ecotoxicity:**

Do not empty into drains / surface water / ground water.
Harmful to aquatic life with long lasting effects.

| Hazardous components CAS-No. | Value type | Value | Acute Toxicity Study | Exposure time | Species | Method |
|-----------------------------------|---------------|--------------|----------------------------|------------------|--|--|
| Acetone 67-64-1 | LC50 | 8.120 mg/l | Fish | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Acetone 67-64-1 | EC50 | 6.098,4 mg/l | Daphnia | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Propan-2-ol 67-63-0 | LC50 | 9.640 mg/l | Fish | 96 h | Pimephales promelas | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Propan-2-ol 67-63-0 | EC50 | 13.299 mg/l | Daphnia | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Propan-2-ol 67-63-0 | EC50 | > 1.000 mg/l | Algae | 96 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Propan-2-ol 67-63-0 | NOEC | 1.000 mg/l | Algae | 96 h | Scenedesmus subspicatus (new name: Desmodesmus subspicatus) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Propan-2-ol 67-63-0 | NOEC | 30 mg/l | chronic Daphnia | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Benzothiazole-2-thiol 149-30-4 | LC50 | 1,6 mg/l | Fish | 96 h | Brachydanio rerio (new name: Danio rerio) | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Benzothiazole-2-thiol 149-30-4 | EC50 | 4,1 mg/l | Daphnia | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Benzothiazole-2-thiol 149-30-4 | EC50 | 0,25 mg/l | Algae | 96 h | Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Benzothiazole-2-thiol 149-30-4 | NOEC | 0,34 mg/l | chronic Daphnia | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

12.2. Persistence and degradability**Persistence and Biodegradability:**

No data available.

| Hazardous components CAS-No. | Result | Route of application | Degradability | Method |
|-----------------------------------|-----------------------|-------------------------|---------------|---|
| Acetone 67-64-1 | readily biodegradable | aerobic | 81 - 92 % | EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test) |
| Propan-2-ol 67-63-0 | readily biodegradable | aerobic | 70 - 84 % | EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test) |
| Benzothiazole-2-thiol 149-30-4 | | aerobic | 2,5 % | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |

12.3. Bioaccumulative potential / 12.4. Mobility in soil**Mobility:**

The product evaporates readily.

Bioaccumulative potential:

No data available.

| Hazardous components CAS-No. | LogKow | Bioconcentration factor (BCF) | Exposure time | Species | Temperature | Method |
|-----------------------------------|---------------|----------------------------------|------------------|---------|-------------|--|
| Acetone 67-64-1 | 0,24 | | | | | |
| Propan-2-ol 67-63-0 | 0,05 | | | | | OECD Guideline 107 (Partition Coefficient (n- octanol / water), Shake Flask Method) |
| Benzothiazole-2-thiol 149-30-4 | 2,34 - 2,5 | | | | | |

12.5. Results of PBT and vPvB assessment

| Hazardous components CAS-No. | PBT/vPvB |
|---------------------------------|---|
| Acetone 67-64-1 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Propane 74-98-6 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Propan-2-ol 67-63-0 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

Disposal must be made according to official regulations.

Waste code

14 06 03 Other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information**14.1. UN number**

| | |
|------|------|
| ADR | 1950 |
| RID | 1950 |
| ADN | 1950 |
| IMDG | 1950 |
| IATA | 1950 |

14.2. UN proper shipping name

| | |
|------|---------------------|
| ADR | AEROSOLS |
| RID | AEROSOLS |
| ADN | AEROSOLS |
| IMDG | AEROSOLS |
| IATA | Aerosols, flammable |

14.3. Transport hazard class(es)

| | |
|------|-----|
| ADR | 2.1 |
| RID | 2.1 |
| ADN | 2.1 |
| IMDG | 2.1 |
| IATA | 2.1 |

14.4. Packaging group

ADR
RID
ADN
IMDG
IATA

14.5. Environmental hazards

| | |
|------|----------------|
| ADR | not applicable |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

14.6. Special precautions for user

| | |
|------|-----------------------------------|
| ADR | not applicable Tunnelcode: (D) |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content 99 %
(1999/13/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapor.
- H280 Contains gas under pressure; may explode if heated.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.