



## Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 13

LOCTITE 572

SDS No. : 454059  
V005.1

Revision: 15.11.2017  
printing date: 26.11.2017

Replaces version from: 06.06.2017

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE 572

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Anaerobic

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Serious eye irritation

H319 Causes serious eye irritation.

Category 2

#### 2.2. Label elements

##### Label elements (CLP):

##### Hazard pictogram:



##### Signal word:

Warning

##### Hazard statement:

H319 Causes serious eye irritation.

**Supplemental information** Contains Linalool. May produce an allergic reaction.

**Precautionary statement:** "\*\*\*\*" \*\*\*For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements\*\*\*

**Precautionary statement:** P337+P313 If eye irritation persists: Get medical advice/attention.  
**Response**

### 2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General chemical description:

Anaerobic adhesive

#### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Octan-1-ol 111-87-5	203-917-6 01-2119486978-10	10- 20 %	Eye Irrit. 2 H319 Aquatic Chronic 3 H412
Cumene hydroperoxide 80-15-9	201-254-7	0,1- < 1 %	Acute Tox. 4; Dermal H312 STOT RE 2 H373 Acute Tox. 4; Oral H302 Org. Perox. E H242 Acute Tox. 3; Inhalation H331 Aquatic Chronic 2 H411 Skin Corr. 1B H314
Linalool 78-70-6	201-134-4 01-2119474016-42	0,1- < 1 %	Skin Sens. 1B H317 Skin Irrit. 2 H315 Eye Irrit. 2 H319

**For full text of the H - statements and other abbreviations see section 16 "Other information".  
Substances without classification may have community workplace exposure limits available.**

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

#### Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

#### **4.2. Most important symptoms and effects, both acute and delayed**

EYE: Irritation, conjunctivitis.

Prolonged or repeated contact may cause skin irritation.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

**Suitable extinguishing media:**

Carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

None known

#### **5.2. Special hazards arising from the substance or mixture**

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

#### **5.3. Advice for firefighters**

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Additional information:**

In case of fire, keep containers cool with water spray.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Wear protective equipment.

#### **6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

#### **6.3. Methods and material for containment and cleaning up**

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

#### **6.4. Reference to other sections**

See advice in section 8

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

**7.2. Conditions for safe storage, including any incompatibilities**

Refer to Technical Data Sheet

**7.3. Specific end use(s)**

Anaerobic

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational Exposure Limits**Valid for  
Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL

**Occupational Exposure Limits**Valid for  
Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, TOTAL INHALABLE DUST]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		IR_OEL

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Octan-1-ol 111-87-5	aqua (marine water)		0,02 mg/l				
Octan-1-ol 111-87-5	sediment (freshwater)				2,1 mg/kg		
Octan-1-ol 111-87-5	sediment (marine water)				0,21 mg/kg		
Octan-1-ol 111-87-5	aqua (freshwater)		0,2 mg/l				
Octan-1-ol 111-87-5	sewage treatment plant (STP)		55,5 mg/l				
Octan-1-ol 111-87-5	soil				1,6 mg/kg		
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	aqua (freshwater)		0,0031 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	aqua (marine water)		0,00031 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	aqua (intermittent releases)		0,031 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	Sewage treatment plant		0,35 mg/l				
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	sediment (freshwater)				0,023 mg/kg		
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	sediment (marine water)				0,0023 mg/kg		
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	soil				0,0029 mg/kg		
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	aqua (freshwater)		0,2 mg/l				
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	aqua (marine water)		0,02 mg/l				
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	aqua (intermittent releases)		2 mg/l				
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	sediment (freshwater)				2,22 mg/kg		
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	sediment (marine water)				0,222 mg/kg		
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	soil				0,327 mg/kg		
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	sewage treatment plant (STP)		> 10 mg/l				

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Octan-1-ol 111-87-5	Workers	dermal	Acute/short term exposure - systemic effects		125 mg/kg	
Octan-1-ol 111-87-5	Workers	inhalation	Acute/short term exposure - systemic effects		220 mg/m3	
Octan-1-ol 111-87-5	Workers	dermal	Long term exposure - systemic effects		125 mg/kg	
Octan-1-ol 111-87-5	Workers	inhalation	Long term exposure - systemic effects		220 mg/m3	
Octan-1-ol 111-87-5	General population	inhalation	Acute/short term exposure - systemic effects		65 mg/m3	
Octan-1-ol 111-87-5	General population	oral	Acute/short term exposure - systemic effects		75 mg/kg	
Octan-1-ol 111-87-5	General population	dermal	Long term exposure - systemic effects		75 mg/kg	
Octan-1-ol 111-87-5	General population	inhalation	Long term exposure - systemic effects		65 mg/m3	
Octan-1-ol 111-87-5	General population	oral	Long term exposure - systemic effects		75 mg/kg	
.alpha.,.alpha.-Dimethylbenzyl hydroperoxide 80-15-9	Workers	inhalation	Long term exposure - systemic effects		6 mg/m3	
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Workers	dermal	Acute/short term exposure - systemic effects		5 mg/kg	
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Workers	inhalation	Acute/short term exposure - systemic effects		16,5 mg/m3	
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Workers	dermal	Acute/short term exposure - local effects		15 mg/cm2	
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Workers	dermal	Long term exposure - systemic effects		2,5 mg/kg	
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Workers	inhalation	Long term exposure - systemic effects		2,8 mg/m3	
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	Workers	dermal	Long term exposure - local effects		15 mg/cm2	
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	General population	dermal	Acute/short term exposure - systemic effects		2,5 mg/kg	
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	General population	inhalation	Acute/short term exposure - systemic effects		4,1 mg/m3	
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	General population	oral	Acute/short term exposure - systemic effects		1,2 mg/kg	
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	General population	dermal	Acute/short term exposure - local effects		15 mg/cm2	
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	General population	dermal	Long term exposure - systemic effects		1,25 mg/kg	
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	General population	inhalation	Long term exposure - systemic effects		0,7 mg/m3	
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	General population	oral	Long term exposure - systemic effects		0,2 mg/kg	
Dimethyl-2,7-Octadien-6-ol, 2,6- 78-70-6	General population	dermal	Long term exposure - local		15 mg/cm2	

effects

**Biological Exposure Indices:**

None

**8.2. Exposure controls:**

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to &gt; 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to &gt; 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance	paste paste, liquid white
Odor	slightly
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	> 93 °C (> 199.4 °F); no method
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable

Density	No data available / Not applicable
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Insoluble
Solubility (qualitative) (Solvent: Acetone)	Soluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

## 9.2. Other information

No data available / Not applicable

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Peroxides.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

No decomposition if used according to specifications.

### 10.5. Incompatible materials

See section reactivity.

### 10.6. Hazardous decomposition products

carbon oxides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

#### Oral toxicity:

May cause irritation to the digestive tract.

#### Skin irritation:

Prolonged or repeated contact may cause skin irritation.

#### Eye irritation:

Causes serious eye irritation.

#### Sensitizing:

May cause allergic reaction.

**Acute oral toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Octan-1-ol 111-87-5	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute Oral Toxicity)
Cumene hydroperoxide 80-15-9	LD50	550 mg/kg	oral		rat	not specified
Linalool 78-70-6	LD50	2.790 mg/kg	oral		rat	not specified

**Acute dermal toxicity:**

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Octan-1-ol 111-87-5	LD50	2.000 - 4.000 mg/kg	dermal		rabbit	Expert judgement
Octan-1-ol 111-87-5	Acute toxicity estimate (ATE)	2.500 mg/kg				
Cumene hydroperoxide 80-15-9	LD50	1.200 - 1.520 mg/kg	dermal			not specified

**Skin corrosion/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
Linalool 78-70-6	moderately irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Linalool 78-70-6	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Octan-1-ol 111-87-5	irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Linalool 78-70-6	not irritating		rabbit	not specified
Linalool 78-70-6	irritating		rabbit	not specified

**Germ cell mutagenicity:**

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Octan-1-ol 111-87-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		Henkel Method
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	not specified

**Repeated dose toxicity**

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	not specified

**SECTION 12: Ecological information****General ecological information:**

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

**12.1. Toxicity****Ecotoxicity:**

Do not empty into drains / surface water / ground water.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Octan-1-ol 111-87-5	LC50	13,3 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Octan-1-ol 111-87-5	EC50	47 mg/l	Daphnia	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Octan-1-ol 111-87-5	EC10	4,2 mg/l	Algae	48 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
	EC50	14 mg/l	Algae	48 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
Octan-1-ol 111-87-5	EC 50	350 mg/l	Bacteria	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Octan-1-ol 111-87-5	NOEC	1 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	EC 50	7 mg/l	Daphnia	24 h	Water flea (Daphnia magna)	
	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide 80-15-9	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	EC10	70 mg/l	Bacteria	30 min		not specified
Linalool 78-70-6	LC50	27,8 mg/l	Fish	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Linalool 78-70-6	EC50	59 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Linalool 78-70-6	EC50	88,3 mg/l	Algae	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
	EC10	38,4 mg/l	Algae	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Linalool 78-70-6	EC0	100 mg/l	Bacteria	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

**12.2. Persistence and degradability****Persistence and Biodegradability:**

The product is not biodegradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Octan-1-ol 111-87-5	readily biodegradable	aerobic	92 %	OECD Guideline 310 (Ready Biodegradability/CO <sub>2</sub> in Sealed Vessels (Headspace Test))
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO <sub>2</sub> Evolution Test)
Linalool 78-70-6	readily biodegradable	aerobic	> 97,1 %	OECD Guideline 301 B (Ready Biodegradability: CO <sub>2</sub> Evolution Test)
	inherently biodegradable		100 %	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)

**12.3. Bioaccumulative potential / 12.4. Mobility in soil****Mobility:**

Cured adhesives are immobile.

**Bioaccumulative potential:**

No data available.

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Octan-1-ol 111-87-5	3,5				23 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Cumene hydroperoxide 80-15-9		9,1		calculation		OECD Guideline 305 (Bioconcentration: Flow-through Fish Test) not specified
Cumene hydroperoxide 80-15-9	2,16					
Linalool 78-70-6	3,1				25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

**12.5. Results of PBT and vPvB assessment**

Hazardous components CAS-No.	PBT/vPvB
Octan-1-ol 111-87-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Cumene hydroperoxide 80-15-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Linalool 78-70-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**12.6. Other adverse effects**

No data available.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

**Product disposal:**

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Collection and delivery to recycling enterprise or other registered elimination institution.

**Disposal of uncleaned packages:**

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

**Waste code**

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

### SECTION 14: Transport information

**14.1. UN number**

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

**14.2. UN proper shipping name**

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

**14.3. Transport hazard class(es)**

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

**14.4. Packing group**

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

**14.5. Environmental hazards**

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

**14.6. Special precautions for user**

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

### SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content < 3 %  
(2010/75/EC)

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

## SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H242 Heating may cause a fire.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**